

Pro Heating PE Series

5 Years Product Warranty

SUNDIRECT Pro Heating PE Series

This series represents the premier choice for the majority of our customers. Due to their unique internal design these panels are even more cost efficient. There are several power ranges available which will be suitable for different types of applications. On top of that every panel is customizable to the needs of every customer.

The carbon crystal heating element

SUNDIRECT Pro heating panel heaters use the carbon crystal heating element which operates at a lower watt density to create a warm and comfortable feeling. On top of that it offers great energy efficiency and enhances performance.

Compared to traditional heating elements, no electromagnetic radiation is created and a more even surface temperature is provided to ensure safety.

State of the art panel design

SUNDIRECT panel heaters have a white surface and white frames by default which ensure a great appearance. All panels live up to state of the art designs and provide simple mounting solutions.



Pro heating PE series





PE270 30*90cm 270W White frame Wall/Ceiling 3-6m² PE350 60*60cm 350W White frame Wall/Ceiling 4-8m² PE540 60*90cm 540W White frame Wall/Ceiling 6-10m² PE700 60*120cm 700W White frame Wall/Ceiling 8-16m² PE1000 80*115cm 1000W White frame Wall/Ceiling 10-20m²	Model	Size	Power	Frame	Mounting	Heated room size
PE540 60*90cm 540W White frame Wall/Ceiling 6-10m ² PE700 60*120cm 700W White frame Wall/Ceiling 8-16m ²	PE270	30*90cm	270W	White frame	Wall/Ceiling	3-6m²
PE700 60*120cm 700W White frame Wall/Ceiling 8-16m ²	PE350	60*60cm	350W	White frame	Wall/Ceiling	4-8m²
, , , , , , , , , , , , , , , , , , ,	PE540	60*90cm	540W	White frame	Wall/Ceiling	6-10m²
PE1000 80*115cm 1000W White frame Wall/Ceiling 10-20m ²	PE700	60*120cm	700W	White frame	Wall/Ceiling	8-16m²
	PE1000	80*115cm	1000W	White frame	Wall/Ceiling	10-20m²



Heating element: Carbon crystal heating element

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m standard EU Plug



Surface temperature: 85-95degree Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life time: up to 100000hours on proper use



Notice:

Please separate the mounting solution for different models as per instruction. Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.






















Sundirect Technology Ltd.





Infinity Heating IC Series

5 Years Product Warranty

SUNDIRECT Infinity Heating IC Series

SUNDIRECT Infinity Heating range is the frameless white infrared panel heater, it's the premium range that Sundirect is offering. The white and frameless design, simple but elegant, fit for any kind of the environment, it's suitable both residential and commercial installations. IC range comes up with 3 powers, differs from 300W to 600W and 800W.

Easy fit mounting

IC series is using Sundirect unique "Easy fit" mounting solution, which is specially designed for easy installation as well as the secure mounting. You can easily mount the IC panels on the wall or ceiling with our "Easy fit" bracket, which is included in the package. Mount the bracket to the wall, and fit the panels to the bracket, slide and block.

Best heating performance

The IC range is equipped with the high infrared emitted white metal surface, together with our high quality carbon crystal heating element and the unique design on the insulation and infrared reflection on the back, which is the guarantee of the energy efficiency. It is one of the best performance infrared panel heaters in the market.



Infinity heating IC series



IC600





Size	Power	Frame	Mounting	Heated room size
60*60cm	300W	Frameless	Wall/Ceiling	4-8m²
65*100cm	600W	Frameless	Wall/Ceiling	7-14m²
70*125cm	800W	Frameless	Wall/Ceiling	9-18m²
	60*60cm 65*100cm	60*60cm 300W 65*100cm 600W	60*60cm 300W Frameless 65*100cm 600W Frameless	60*60cm 300W Frameless Wall/Ceiling 65*100cm 600W Frameless Wall/Ceiling



Heating element: Carbon crystal heating element

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m EU standard Plug



Surface temperature: 85-95degrees celsius

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life span: up to 100000 hours with proper usage



Please separate the mounting solution for different models as per instruction. Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.



















Sundirect Technology Ltd.





Glass Heating GD Series

5 Years Product Warranty

SUNDIRECT Glass Heating GD Series

SUNDIRECT glass infrared panel heaters are made from high quality toughened safety glass combining sophisticated design with optimum safety and energy efficiency. This sleek beautiful design will enhance your home or office with class and elegance but also guarantees an improved level of comfort.

Every room is different

Our glass panels come in different sizes and power outputs to suit every requirement and is available in various colors. This series is perfectly suitable for modern decorations and the needs of the 21st century.

More control, lower costs

SUNDIRECT far infrared panels offer owners an unprecedented level of control over their property's temperature and energy use. Installations using our infrared panels save up to 55 percent of the energy consumption.



Glass Heating GD series



GD500

GD700



Model	Size	Power	Frame	Mounting	Heate
GD350	66*66cm	350W	Frameless	Wall	d
GD500	60*100cm	500W	Frameless	Wall	room
GD700	70*130cm	700W	Frameless	Wall	size



Heating element: Carbon crystal heating element

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m EU standard Plug



Surface temperature: 85-95degrees celsius

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life span: up to 100000 hours with proper usage



Please separate the mounting solution for different models as per instruction. Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.

























Mirror Heating MD Series

5 Years Product Warranty

SUNDIRECT Mirror Heating MD Series

SUNDIRECT mirror heaters provide you with clear vision and warmth and are characterized not only by their elegance but also by their heating advantage. The mirror does not fog up under high humidity levels because of the very special characteristics of infrared waves. Therefore our mirror heaters are perfect for installing in your bathroom or spa apart from the fact that you can place it in any living environment as well.

Thin, stylish, frameless

The frameless SUNDIRECT infrared heating panel is not only very thin but also extremely stylish. No matter the size you choose, the thickness of the panel remains the same. The heating panel adapts to the style of every room and disguises the fact that it contains a heating element in a very elegant way. Since it can be customized the panel looks absolutely amazing in any modern environment.

Slick and modern

The framed SUNDIRECT infrared heating panel comes with a thin frame offering a customizable alternative to the frameless version. The panel maintains its stylish and modern design while it provides you with even more options.




Mirror Heating MD series



MD500





Model	Size	Power	Frame	Mounting	Heated room size
MD300	66*66cm	350W	Frameless	Wall	3-6m ²
MD500	60*100cm	500W	Frameless	Wall	6-10m ²
MD700	70*130cm	700W	Frameless	Wall	8-15m ²



Heating element: Carbon crystal heating element

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m EU standard Plug



Surface temperature: 85-95degrees celsius

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life span: up to 100000 hours with proper usage



Notice:

Please separate the mounting solution for different models as per instruction. Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.




















Sundirect Technology Ltd.

info@sundirect-heater.com www.sundirect-heater.com





Round Heating RC500-W

5 Years Product Warranty

Sundirect round panel heaters set themselves apart with their round and frameless appearance. The simple and modern design fit perfectly into modern living environments. Round panels are available with a white steel or mirror surface. Sundirect is one of very few companies on the market offering this unique design.

ModelSizePowerSurfaceMountingHeated room sizeRC500-W70*70cm500WSteelWall/ceiling5-10m²

Heating element: Silicon heating wire

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m EU standard Plug

Surface temperature: 110-120 degrees celsius on the wall

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP45

Life span: up to 100000 hours with proper usage

Notice

Please separate the mounting solution for different models as per instruction.

Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.





Round Heating RC350-M

5 Years Product Warranty

Sundirect round panel heaters set themselves apart with their round and frameless appearance. The simple and modern design fit perfectly into modern living environments. Round panels are available with a white steel or mirror surface. Sundirect is one of very few companies on the market offering this unique design.

Heating element: Silicon heating wire

70*70cm

Insulation material: Fiberglass

Size

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 3pcs Plug: 2.5m EU standard Plug

Surface temperature: 85-95degrees celsius on the wall

Power

350W

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life span: up to 100000 hours with proper usage

Notice:

Model

RC350-M

Please separate the mounting solution for different models as per instruction.
Use our online heating calculator (http://www.sundirect-heater.com/technology/calculator) to correctly design the heating system for each room.

Surface

Mirror

Mounting

Wall

Heated room size

3-7m²





Desk Heating IC150

5 Years Product Warranty

Sundirect IC150 is the mini version of IC series. It has the same white frameless design, specially designed and optimized to be used under the desk. With the bracket provided, it can be easily fixed under or to the side of the desk. Pair it with our aluminum feet stand BS003 to make it portable. Using our desk heater, you will never get cold feet again!

ModelSizePowerSurfaceMountingIC15032*62cm150WSteelWall/desk

Heating element: Carbon crystal heating element

Insulation material: Fiberglass

Reflection: Steel reflection layer with white finish

Over heat protection sensors: 1pc Plug: 2.5m EU standard Plug

Surface temperature: 80-90degrees celsius under the desk

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IP44

Life span: up to 100000 hours with proper usage




Sundirect Technology Ltd.

info@sundirect-heater.com www.sundirect-heater.com Sundirect and the Sundirect Logo are registered Trademarks of Sundirect Technology Ltd. © 2017 Sundirect Technology Ltd. All rights reserved.

Specifications included in this data sheet are subject to change without notice.





Space Heating SC Series

5 Years Product Warranty

SUNDIRECT Space Heating SC Series

The stylish and innovative Sundirect Space Heating Series is specifically designed to heat the big rooms and also outdoor. It has a high quality extrude and anodized Aluminum body, which has additional infrared boost coating on the surface, together with the high quality Chromium Aluminum heating element, the heater emits strong far infrared wave. It's one of the highest efficient far infrared space heater in the market.

Hotter emitter, quicker heating SC series uses the higher temperature iron Chromium Aluminum emitter, which operates at a surface temperature of 300-350 degrees. Due to the higher surface temperature, the infrared ray is stronger, can reach a longer distance and be heat up quickly. It takes less than 5 minutes to heat at the maximum surface temperature.

Massive application

The new Space Heating series is the ideal heating solution for all kind of the space and commercial heating, like office reception areas, shops, hotels, churches, restaurants, bars, public halls and also anywhere outside with the cover like terrace and so on. There is no red glow, maintenance free, which is a good option to replace the traditional quartz and halogen heaters.



DATASHEET Space heating SC series





 Model
 Size
 Power
 Mounting
 Heated room size

 SC1800
 1050*150*63mm
 1800W
 Wall/Ceiling
 8-12m²

 SC2400
 1350*150*63mm
 2400W
 Wall/Ceiling
 13-18m²



Insulation material: Fiberglass

Reflection material: Steel reflection layer Over heat protection sensors: 1pc

Surface temperature: 300-350 degrees celsius

Energy efficiency: up to 95% Voltage: 220-240V, 50Hz

Protection: IPX4

Certification: CE, ROHS



NIadiaa.

The SC series are not equipped with plug due to the regulation, please make sure the cable used to connect to the existing wiring should be correctly rated solid core wiring cable. Please note that the use of flexible appliance cable with stranded conductors for permanent wiring (except for the final connection between a cable outlet and the fixed equipment) is prohibited by IEE wiring regulations.

The heater is designed to be used in outdoor space where the air movement is small, if use them in a big wind movement area, please be noticed that the heating performance might be decreased. As a solution, we will suggest you to mount the heater closer to the heating objects to get a better performance.



Thermostat





SD-T4001 acts as a basic plug-in thermostat. You simply connect the heater and the thermostat to control your room temperature resulting into energy savings.

Specification:

Output Voltage: 230V

Switching Capacity: 3600W/16A Temperature settings: 5°C ~35°C

Accuracy: +/- 0.5°C IP protection rating: 20 Non-programmable



Specification:

Output Voltage: 230V

Switching Capacity: 3600W/16A Temperature settings: 5°C ~35°C

Accuracy: +/- 0.5°C IP protection rating: 30 5+1+1 programmable



SD-T4003 acts as a combination of the basic plug-in version together with a remote control. You can simply plug the panel and use the remote control to control the room temperature. It also offers the so called "5+1+1 program" with 4 available time zones.

Specification:

Output Voltage: 230V

Switching Capacity: 3600W/16A Temperature settings: 5°C ~35°C

Accuracy: +/- 0.5°C IP protection rating: 30 5+1+1 programmable





SD-T4004 acts as a combination of a box receiver and a wireless remote control. The box receiver allows you to hide the cable behind the wall to improve the appearance as well as gaining all the temperature and energy saving benefits. It also offers the so called "5+1+1 program" with 4 available time zones.

Specification:

Output Voltage: 230V

Switching Capacity: 3600W/16A Temperature settings: 5°C ~35°C

Accuracy: +/- 0.5°C IP protection rating: 30 5+1+1 programmable



Sundirect Technology Ltd.

info@sundirect-heater.com www.sundirect-heater.com Sundirect and the Sundirect Logo are registered Trademarks of Sundirect Technology Ltd. © 2017 Sundirect Technology Ltd. All rights reserved.

Specifications included in this data sheet are subject to change without notice.



Accessories











Model: BC002

Using the ceiling mounting set BC002 enables you to hang the panel up to 1m below the ceiling. It's the perfect solution for areas which require the panel to be in a lower position.

Model: BC004/BC005

The ceiling mounting bracket guarantees easy installation for PE panels. Simply fix the bracket on the ceiling and install the panel. It allows you to mount the panel as close to the ceiling as possible.

BC004 fits the models of PE350/PE540/PE700/PE1000 BC005 fits PE270

Model: TR001/TR002

TR001/TR002 is made of stainless steel and acts as an optional accessory for the glass and mirror heater. By using the towel rail you can add a towel warmer trait to your glass and mirror heaters.

TR001 fits the models of GD350/GD500/MD350/MD500 TR002 fits the models of GD700/MD700

Model: BS003

BS003 is a white feet stand made of Aluminium and is specially designed for PE series.

Model: BS004

BS004 is the white steel feet stand, it was designed for fit all the models expect the round heaterRC series. Simply place the panel on the bracket and tighten the screws from the back side. Using BS004 and makes your Sundirect infrared heater portable.



Sundirect Technology Ltd.

info@sundirect-heater.com www.sundirect-heater.com Sundirect and the Sundirect Logo are registered Trademarks of Sundirect Technology Ltd. © 2017 Sundirect Technology Ltd. All rights reserved.

Specifications included in this data sheet are subject to change without notice.