



DATASHEET Outdoor Infrared heater OC Series

3 Years Product Warranty

The OC Series represents powerful outdoor heaters offered exclusively by Sundirect and is designed for outdoor heating only. It offers more power and concentrated heating compared to our hybrid Space Heater SC Series, making it perfectly suitable for windy uncovered outdoor areas. The OC Series is rated IP65, making it waterproof and usable for most outdoor applications. Its unique ultra low light carbon fibre heating element is the key difference compared to existing outdoor heaters on the market using mostly halogen or quartz. This grants a longer lifespan and higher energy efficiency. The OC Series emits long wave infrared (300-350W) creating a light glow and cozy warmth rather than heat. The integrated control system allows operation of 2 power levels using a simple remote control. You can easily adjust the power settings of the heater and also turn it on/off remotely. There are 2 power settings available (50%/100%) which means you are flexible and able to adjust to different applications.



DATASHEET Outdoor Infrared heater OC series





Model	Size
OC2000	72*12
OC2500	77*12

2*12mm 2*12mm Power 2000W 2500W Mounting Wall only Wall only Heated Area 10-20m² 12-25m²

Heating element: Ultra low light carbon fibre heating element Surface temperature: 300-350 degrees celsius Reflection material: Aluminum reflection layer Plug: 1.9m EU standard Plug

Energy efficiency: up to 95% Voltage: 220~240V, 50Hz Protection: IP65 Power switch: YES Power setting: 2 levels Remote control: YES Lifespan: 6000 working hours under proper usage Certification: CE, ROHS

Notice:

The Sundirect OC Series represents infrared heaters ONLY designed for outdoor heating purposes so please notice that they MUST NOT be used indoors or in other kind of applications.



Sundirect Technology Ltd.

info@sundirect-heater.com www.sundirect-heater.com Sundirect and the Sundirect Logo are registered Trademarks of Sundirect Technology Ltd. © 2018 Sundirect Technology Ltd. All rights reserved. Specifications included in this data sheet are subject to change without notice.